Technical Bulletin Hookclean

Heavy Duty Alkaline Cleaner & Rust Remover

Product Description:

HOOKCLEAN is a technologically advanced compound for the cleaning and derusting of meat rollers, slides and gambrels. Animal fat, grease, and rust are removed by the simple hot tank process. AQIS APPROVED UNDER CATEGORY 11 FOR USE AS A LUBRICANT TYPE B.

Application:

PROCEDURE 1: HOOKS IN GOOD CONDITION OR SMALL THRU-PUT
STEP 1 Use HOOKCLEAN at 100 grams per litre water at 82oC to 87oC.
STEP 2 Hot overflow rinse.
STEP 3 Immerse in HOOKDIP dewatering inhibitor.

PROCEDURE 2: HOOKS IN REASONABLE CONDITION OR FOR HIGH THRU-PUT

STEP 1 Pre clean with HOOKCLEAN at 25 grams per litre at 82oC to 87oC.

- STEP 2 Preclean with HOOKCLEAN at 100 grams per litre at 82oC to 87oC.
- STEP 3 Hot overflow rinse.

STEP 4 Immerse in HOOKDIP dewatering inhibitor.

PROCEDURE 3:

Where a brighter finish is required include a tank of HOOKBRITE at a strength of 1:40 with water. Use this step prior to coating with HOOKDIP.

HOOKCLEAN contains caustic soda and contact with the skin should be avoided. Wear protective clothing. Never add HOOKCLEAN to hot water.



SHELF LIFE: As a quality assured manufacturer, Castle Chemicals has a stringent Quality assurance programme. As part of this regime, the label on this product shows a batch number and date of manufacture. This product has a shelf life of 24 months from the label printed date of manufacture. This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Castle Chemicals assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of material.

Page 1 of 1

CASTLE CHEMICALS

16 Rural Drive Sandgate NSW 2304 | Ph: 02 4014 5555 | Fax: 02 4968 4883 | ccsales@castlechem.com.au | www.castlechem.com.au