

Technical Bulletin

Kemsteam

Chemical Steam Cleaning

Product Description:

KEMSTEAM is a strongly alkaline heavy duty liquid with excellent hard water tolerance. KEMSTEAM is described as a "Quick Break Detergent" and has been tested to break within the 10 minute parameter.

KEMSTEAM is safe to use on:

- tin
- zinc
- ceramic and glass
- plastic
- well bonded painted surfaces (at correct dilution)

Application:

KEMSTEAM is designed for the removal of mineral oil and road grime, but is excellent for animal fats, polymerised oil, carbonaceous soils, proteinaceous soils and some paints.

KEMSTEAM should be used in a concentrate tank at the following dilutions.

Heavy Soil Areas: 1:10

Medium Soil Areas: 1:30

Light Soil Areas: 1:50

For operator safety, full protective clothing should be worn.

SHELF LIFE: As a quality assured manufacturer, Castle Chemicals has a stringent Quality assurance programme. As part of this regime, the label on this product shows a batch number and date of manufacture. This product has a shelf life of 24 months from the label printed date of manufacture. This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Castle Chemicals assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of material.

Page 1 of 1