



S1 Pre-Soak

Premium Pre-Treatment / Heavy Duty Vehicle Wash

Code: 33128

Product Description:

S1 Pre-Soak is a strong, heavy duty vehicle wash designed specifically to remove dirt, soils, and road stains from trucks, cars, buses and all forms of on and off-road transport.

S1 Pre-Soak is a complex blend of surfactants, sequestering agents, corrosion inhibitors, natural solvents and phosphates to ensure a thorough clean, effortlessly. It is safe for use on all metals.

S1 Pre-Soak is a high foaming product that can be sponged, broomed or sprayed onto bodywork, glass, aluminium and all types of truck curtains. It has remarkable rinsing capabilities and will not streak when hosed effectively.

- Quickly removes all dirt and road grime.
- Highly effective at removing exhaust staining.
- Free rinsing - no streaks.
- High foaming - longer contact time.
- Safe on all surfaces. Including fabric and plastic curtains.
- Will not attack paintwork or chrome. Built in corrosion inhibitors.
- Very economical to use.

Dark red, liquid with a distinct citrus fragrance. S1 Pre-Soak is water soluble at all use solutions.

pH (1% solution) typically: 11.5-12.0

pH (neat): 12.0-12.5

Application:

Generally used at a concentration of 5-10% (50-100 mL/L). Can also be used neat as a degreaser. When using a high-pressure cleaner, the dose rate is 10-20 mL/L. If time permits, sponge or brush surface. If not, allow to penetrate for as long as possible. Hose or pressure rinse off all residual suds. It is most effective to rinse from the bottom up to the top and back down to the bottom again. This rinses soils from crevices. If practical, chamois all paintwork for a great result.

Storage:

Store in the original, tightly closed container in a cool, dry place away from direct sunlight and extreme temperatures. Protect from frost. Recommended storage temperature: 5–30 °C.

SHELF LIFE: As a quality assured manufacturer, Castle Chemicals has a stringent Quality Assurance programme. As part of this regime, the label on this product shows a batch number and date of manufacture. This product has a shelf life of 12 months from the label printed date of manufacture. This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Castle Chemicals assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of material.